

260MRT Diesel/Engine Scissor Lift



Proportional drive gives smooth control

One handed operation for operator comfort and control

Compact size for ease of access through double doorways after lowering fold-down handrails

Low maintenance non-skid steel platform with extension deck and Load Sensing System

Minimum hydraulic components reduce maintenance and operating costs

Kubota D1005 diesel engine for rough terrain capability

Hydraulic piston drive motors for 4 wheel drive maximum traction and ease of steering

Tie down and lifting lugs for ease of transport

Auto level stabilisers with side to side operator selectable final trim

Non-marking urethane filled lug tyres

QUESTIONS TO ASK

- What are the ground conditions in the work area?
- Is the site level, will you need auto level stabilisers?
- What is the rated capacity needed for the job, 565kg?
- Do you need an extension lead outlet in the platform?
- Do you need non-marking tyres?
- Is there power available on the site?

KEY SELLING POINTS

- Smooth control, proportional drive, with two speed ranges
- Kubota D1005 diesel engine with increased HP output
- Fold-down rails allows drive through a 203cm door
- Extension platform has fold-down rails
- Urethane filled non-marking lug tyres
- Steering with tight 213cm turning radius
- Constant traction 4 wheel drive for 35 per cent gradeability
- Wide scissor stack provides rigidity and stability
- Extended stabilisers prevent drive
- Auto level stabiliser feature allows adjust lateral stabiliser levelling from steer switch
- Multi axis 4 degree level sensor
- Plug in JLG analyser to indicate system functions for servicing and adjustment
- Removable platform control box

APPLICATIONS

- Facilities maintenance
- Shopping centres and other outdoor areas
- Manufacturing and warehouse applications
- Electricians
- Plumbers
- Wall panel installers
- All maintenance and construction work
- Aircraft maintenance, outdoor rated 2 persons
- Tilt up panel building and factory fit outs

SPECIFICATIONS

Performance:

Platform Height (max.)	7.92m
Working Height	9.92m
Lift Time	37 sec
Lower Time	24 sec
Platform Capacity Standard	570kg

Dimensions:

Stowed Height - Rails Up	2.37m
Stowed Height - Rails Lowered	1.47m
Minimum Transport Length (Outriggers)	3.53m
Overall Width	1.75m
Wheelbase	1.98m
Ground Clearance	0.20m
Platform Width	1.65m
Platform Length	2.59m
Standard Platform Extension	1.22m
Platform Height Lowered	1.26m
Maximum Drive Height	7.92m

Power:

Power Source	Diesel
Engine Make	Kubota
Engine Model	1005
Engine Power	17.5kW
DC Voltage	12V
DC Power	850CCA
Drive Motors - Type	Piston
Hydraulic Pump - Type	Gear
Hydraulic Pump Drive Motor Type	Piston

Travel:

Tyre Size	26 x 12
Tyre Type	Urethane Filled/ Non-marking
Inside Turn Radius	2.13m
Outside Turn Radius	4.39m
Drive Speed Elevated	0.6km/h
Gradeability	35%

Weights and Capabilities:

Fuel Tank Capacity	28.39 Ltr
Hydraulic Tank Capacity	56.78 Ltr
Operating Weight	3,700kg